

Oil Removal Filter Cartridges

Features:

- Remove oil from chilled water, hot water, condensate & blowdown.
- Delivered as a dry cartridge, no liquids or chemicals.
- Absorbs oil without absorbing water.
- Permanent immobilization of the oil in the MYCELX cartridge. No desorption.
- Instant, permanent and complete oil removal upon contact.
- Safe and easy to handle.
- Maximum operating pressure differential - 35PSID.



Model #	Dimensions	Micron	Max Temp °F	pH Range	Case Pack
HRM Series Melt Blown Polypropylene with MYCELX Chemistry					
MD10S5	2.5" OD x 10" L	5	160 °F	3-11	4
MD20S5	2.5" OD x 20" L	5	160 °F	3-11	4
MD30S5	2.5" OD x 30" L	5	160 °F	3-11	4
MD40S5	2.5" OD x 40" L	5	160 °F	3-11	4
MD10LD5	4.5" OD x 10" L	5	160 °F	3-11	5
MD20LD5	4.5" OD x 20" L	5	160 °F	3-11	5
HT Series Wound Cotton - Stainless Core with MYCELX Chemistry					
MCW10S5SS	2.5" OD x 10" L	5	210 °F	5-10	4
MCW20S5SS	2.5" OD x 20" L	5	210 °F	5-10	4
MCW30S5SS	2.5" OD x 30" L	5	210 °F	5-10	4
MCW40S5SS	2.5" OD x 40" L	5	210 °F	5-10	4

