

# BAG FILTER HOUSINGS

## QFP Series Bag Filter Housings

offer an economical solution to your commercial and industrial bag filtration applications. These heavy duty housings are designed for maximum durability. The swing bolt closure with eye hooks allows for quick and easy bag change outs.

Housings are available for size # 1 or #2 filter bags in your choice of 304L SS, 316L SS, or carbon steel.

### Features;

- Swing Bolt Closure – Single Bag
- Adjustable Stainless Steel Leg Assembly – Single Bag
- Swing Bolts with Davit Assist Closure – Multi-Round
- Heavy Duty Welded on Mounting Legs – Multi-Round
- Stainless Steel Support Basket(s) with 1/8" Perforations
- Buna N Gasket
- 1/4" Vent and Gauge Ports
- Drain Port
- Housings Rated at 150 PSI, 300°F



Model #	Material	Bag Size	Bag Dimension	# OF Bags	Flow GPM*	Pipe Size	Drain Port
QFPBH1-304	304L	1	7" X 16"	1	60	2.0" FNPT	1/2"
QFPBH1-316	316L	1	7" X 16"	1	60	2.0" FNPT	1/2"
QFPBH1-CS	CARBON	1	7" X 16"	1	60	2.0" FNPT	1/2"
QFPBH2-304	304L	2	7" X 32"	1	120	2.0" FNPT	1/2"
QFPBH2-316	316L	2	7" X 32"	1	120	2.0" FNPT	1/2"
QFPBH2-CS	CARBON	2	7" X 32"	1	120	2.0" FNPT	1/2"
QFP2BH2-304	304L	2	7" X 32"	2	240	3.0" Flange	3/4"
QFP3BH2-304	304L	2	7" X 32"	3	360	4.0" Flange	3/4"
QFP4BH2-304	304L	2	7" X 32"	4	480	4.0" Flange	3/4"
QFP5BH2-304	304L	2	7" X 32"	5	600	6.0" Flange	3/4"
QFP6BH2-304	304L	2	7" X 32"	6	720	6.0" Flange	3/4"
QFP8BH2-304	304L	2	7" X 32"	8	960	8.0" Flange	3/4"
PGS-200-1/4	1/4" Pressure Gauge Set (2), 0-200 PSI, Glycerin Filled						

\*Flow rates are guidelines only. Actual flow rates vary based upon fluid, viscosity, micron ratings and other factors.



Quantrol Inc. 9001 Hanslik Court, Naperville, IL 60564  
Phone: (630) 355-3330 Fax: (630) 355-3568 www.quantrol.net