

SINGLE CARTRIDGE HIGH FLOW BAND CLAMP HOUSINGS

QFP Series High Flow Band Clamp Filter Housings

are designed for Commercial and Industrial liquid filtration applications. The high flow, pleated filter cartridge with inside/outside flow allows for easy, mess free change outs & extended service intervals.

Housing Features;

- Heavy Duty 304 or 316 Stainless Steel Construction
- Durable Bead Blast Finish
- Welded on Mounting/Support Legs
- Easy Access Band Clamp Closure
- Single Cartridge Convenience
- Housing Rated at 150 PSI, 300°F
- 2.0" FNPT Inlet / Outlet
- 1/2" Drain Port & 1/4" Vent Port

Cartridge Features;

- All Polypropylene Construction
- Pleated Media for Long Service Life
- 25 Sq Foot of Surface Area
- Fast & Easy Push / Pull Installation
- O-Ring Seal Eliminates Bypass
- High Flow Capability up to 150 GPM
- Inside Out Flow Retains Particulate During Servicing
- FDA Listed Materials
- Maximum Temperature 170°F
- Recommended Change Out = 30 PSID



Quantrol Part Number	Description
QFPHFE-304	CARTRIDGE HOUSING HIGH FLOW 304 SS 150 GPM 2" FNPT
QFPHFE-316	CARTRIDGE HOUSING HIGH FLOW 316 SS 150 GPM 2" FNPT
QFPHFEC0.5	QFP HFEC CARTRIDGE PP 0.5 MICRON 6" X 23" MAX FLOW 60 GPM
QFPHFEC1	QFP HFEC CARTRIDGE PP 1.0 MICRON 6" X 23" MAX FLOW 80 GPM
QFPHFEC5	QFP HFEC CARTRIDGE PP 5.0 MICRON 6" X 23" MAX FLOW 120 GPM
QFPHFEC10	QFP HFEC CARTRIDGE PP 10 MICRON 6" X 23" MAX FLOW 150 GPM
QFPHFEC20	QFP HFEC CARTRIDGE PP 20 MICRON 6" X 23" MAX FLOW 150 GPM
QFPHFEC50	QFP HFEC CARTRIDGE PP 50 MICRON 6" X 23" MAX FLOW 150 GPM
QFPHFEC70	QFP HFEC CARTRIDGE PP 70 MICRON 6" X 23" MAX FLOW 150 GPM
8017-B	QFP HFEC REPLACEMENT BUNA GASKET

