

JCWTC SERIES STRING WOUND JUMBO CARTRIDGES

For JGCHB Jumbo Cartridge Housings

- Natural Cotton Yarn
- Tin Plated Steel Core
- 300° F Max Temperature Rating
- Choice of Micron Ratings
- Economical

Maximum Recommended Operating Conditions

Differential Pressure.....20-25 PSID

Temperature.....300° F

Typical Applications

- Closed Loop Heating Systems
- Closed Loop Chilled Systems
- Cooling Towers
- Process Water



Construction Materials

- Natural Cotton Yarn
- Tin Plated Steel Core

Dimensions

Outside Diameter....7.75"

Jumbo 40.....9.625" Long

Jumbo 90.....19.5" Long

Jumbo 170.....30.75" Long

Ordering Information

	HOUSING MODEL		
	GJCHB402M2615PC	GJCHB902M2615PC	GJCHB1702M2615PC
1 Micron	JCWTC1-40	JCWTC1-90	JCWTC1-170
5 Micron	JCWTC5-40	JCWTC5-90	JCWTC5-170
20 Micron	JCWTC20-40	JCWTC20-90	JCWTC20-170
50 Micron	JCWTC50-40	JCWTC50-90	JCWTC50-170
100 Micron	JCWTC100-40	JCWTC100-90	JCWTC100-170



Quantrol Inc. 9001 Hanslik Court, Naperville, IL 60564
Phone: (630) 355-3330 Fax: (630) 355-3568 www.quantrol.net