

MBJ SERIES MELT BLOWN CARTRIDGES

For JUMBO CARTRIDGE HOUSINGS

- Spun bonded 100% polypropylene media for economical and efficient filtration
- Provides effective depth filtration when filtering gelatinous / semi-solid particulate from a fluid stream
- Polypropylene construction offers high level of chemical compatibility
- No glues or additives which could foam, discolor or cause other undesirable effects
- Fits most Jumbo type housings including QFP, Harmsco, Flowmatic and Shelco
- Manufactured in the USA

Specifications

Differential Pressure Maximum.....35 PSID
Recommended Change Out.....25 PSID
Temperature Maximum.....140 F° (60° C)

Construction Materials

Filtration Media: Melt Blown Polypropylene
Gaskets: Buna N
End Caps: Polypropylene
Core: Polypropylene

Dimensions

7-3/4" OD X 9-5/8", 19-1/2" and 30-3/4"L

Typical Applications

Closed Loops
Glycol
RO Pre-filtration
Chilled Water
Wastewater
Food & beverage
Oils & Solvents



MBJ Ordering Information

Micron Rating	Jumbo 40, 9-5/8" Length Recommended flow =<25 GPM	Jumbo 90, 19-1/2" Length Recommended flow =<50 GPM	Jumbo 170, 30-3/4" Length Recommended flow =<75 GPM
1	MBJ-40-01	MBJ-90-01	MBJ-170-01
5	MBJ-40-05	MBJ-90-05	MBJ-170-05
20	MBJ-40-20	MBJ-90-20	MBJ-170-20
50	MBJ-40-50	MBJ-90-50	MBJ-170-50
100	MBJ-40-100	MBJ-90-100	MBJ-170-100



Quantrol Inc. 9001 Hanslik Court, Naperville, IL 60564
Phone: (630) 355-3330 Fax: (630) 355-3568 www.quantrol.net