

Seko TCK Series

SEKO Tekna TCK Series Pump Features



- 3 Operating Modes
 - 7 Day timer with 10 ON/OFF programs
 - Volume feed activated manually or by dry contact input (water meter)
 - Manual speed control
- Intuitive user interface with 6 button keypad and LCD display
- Start/Stop button
- Alarm and stroke LED indicators
- Remote Start/Stop input
- Flow and low level inputs
- Alarm dry contact
- Turndown ratio 100:1 using the manual stroke rate control
- Installation flexibility with both wall mount and surface mount brackets included
- Wet end construction of PVDF head, PVDF fittings, ceramic balls, FPM or EPDM seats and a long life, 1 piece, molded PTFE diaphragm.
- Pump head incorporates an integral manual priming valve
- Installation kit included with Foot Valve/Strainer Injection/Back pressure valve, 3/8" PVC suction tubing, 3/8" polyethylene discharge tubing and 1/4" bleed tubing
- Liquid end, user interface and wiring are all on same end of the pump to simplify installation, operation and maintenance
- Chemical resistant, glass reinforced polypropylene enclosure is IP65 and NEMA 4x rated
- Auto ranging power supply, 100-240 VAC, 50/60Hz

Tekna TCK Series, PVDF/TFE/FPM/Ceramic									
Model #	SPM (Max)	GPH	PSI	GPH	PSI	GPH	PSI	GPH	PSI
TCK603NHH0U00	160	1.1	174	1.4	145	1.6	116	2.2	29
Tekna TCK Series, PVDF/TFE/EPDM/Ceramic									
Model #	SPM (Max)	GPH	PSI	GPH	PSI	GPH	PSI	GPH	PSI
TCK603NHH1U00	160	1.1	174	1.4	145	1.6	116	2.2	29

