

NEW!

ULTRAPEN™ PT5

**Dissolved Oxygen (DO)
and Temperature Pen**

Professional Water Analysis

HIGH PERFORMANCE FEATURES

- Industry Leading Accuracy
- Adjustable for Altitude and Salinity
- 3 Calibration Methods: Air, Water and 0 ppm DO
- Dynamic Membrane Temperature Correction
- Easy to Use - One Button Control
- Waterproof
- Rugged Design with Aircraft Aluminum Body
- Proprietary Sensor Design

PT5 COMES WITH:

- PT5 Pocket Tester Pen - Battery Installed
- Protective Cap
- Pocket Clip
- Holster
- Lanyard
- Operating Instructions



instrument shown larger than actual size

ALSO AVAILABLE!

ULTRAPEN™ PT1
Conductivity, TDS, Salinity
& Temperature



ULTRAPEN™ PT2
pH & Temperature



ULTRAPEN™ PT3
ORP & Temperature



ULTRAPEN™ PT4
Free Chlorine Equivalent (FC)
& Temperature



**MYRON L[®]
COMPANY**

Water Quality Instrumentation
Accuracy • Reliability • Simplicity



MADE IN USA

... Since 1957


PT5 MEASUREMENT MODES

| Mode | PARAMETER MEASURED |
|------|--|
| Hold | Displays real-time readings until stable or 3 minutes, whichever ever comes first, then displays final readings. |
| LIVE | Displays real-time readings continuously for up to 5 minutes. |

PT5 PARAMETER MODES

| Mode | PARAMETER MEASURED |
|------------------|---|
| DO Default | Display alternates between DO Concentration in ppm, DO Saturation in % and Temperature. |
| DO Concentration | Display alternates between DO Concentration in ppm and Temperature. |
| DO Saturation | Display alternates between DO Saturation in % and Temperature. |

SPECIFICATIONS

| | |
|---|---|
| Measurement Range: | DO Concentration: 0 - 20 ppm, DO Saturation 0 - 200% Temperature: 0 - 71° C / 32 - 160° F |
| Accuracy: | DO: ± 2% of Reading, Temperature: ± 0.1°C / ± 0.1°F |
| Repeatability: | DO: ± 1% of Reading, Temperature: ± 0.1°C / ± 0.1°F |
| Resolution: | DO Concentration: 0.01 ppm, DO Saturation 0.1% Temperature ± 0.1°C / ± 0.1°F |
| Altitude Adjustment: | -2,000 ft to 15,000 ft: increments of 100 ft |
| Salinity Adjustment: | 0 - 50 ppt increments of 1 ppt |
| Time to Reading Stabilization: | 10 - 180 seconds |
| Active Mode Power Consumption: | Active Mode: 33 - 140 mA, Sleep Mode: 2 µA |
| Temperature Adjustment for Membrane permeability: | Automatic |
| Physical Dimensions: | 17.15 cm L x 1.59 cm D or 6.75 in. L x .625 in. D |
| Weight: | 57.4 g or 2 oz |
| Case Material: | Anodized Aluminum with Protective Coating |
| Battery Type: | N type, Alkaline 1.5 V |
| Calibration Methods: | 1 or 2 Point; 0 ppm DO Calibration Solution and/or air or water |
| Operating Temperature: | DO Saturation: 0 - 60°C / 32 - 140°F; DO Concentration: 0 - 40°C / 32 - 104°F |
| Storage Temperature: | 0 - 55°C / 32 - 131°F |
| Water Resistance: | IP67 and NEMA 6 |
| EN61236-1: 2006 - Annex A: 2008; 1999/5/EC Annex III |  Electrostatic discharge to case of instrument may cause PT5 to spontaneously power on. In this case, the PT5 will power off after several seconds |

ACCESSORIES

STANDARD SOLUTIONS:

Order Model:

DOSOL 0 ppm Dissolved Oxygen Calibration Solution

REPLACEMENT ITEMS AND CONSUMABLE ITEMS:

Order Models:

DOM5 DO Membrane 5pk.

DOSRE DO Sensor Replenishment Electrolyte 2 oz.

DORS DO Replenishment Syringe w/Tip

DOM5K DO Membrane 5pk, Replenishment Electrolyte 2 oz, Syringe w/Tip Kit.

MYRON L® WARRANTY

The PT5, excluding the Sensor and Battery, has a one (1) year limited warranty.

2450 Impala Drive
Carlsbad, CA 92010-7226 USA
Tel: +1-760-438-2021
Fax: +1-800-869-7668 / +1-760-931-9189
www.myronl.com

Built On Trust. Founded in 1957, the Myron L® Company is one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

